



# S-1316AH SHUR-LOC® Handle Eye Hook

www.thecrosbygroup.com

## GET A GRIP ON YOUR LOAD

The SHUR-LOC® Handle Eye Hook gives you better control of your load without compromising the operator's safety. The new ergonomic handle is roomy enough for use with almost any size gloved hand for complete control over the hook and load. Made with forged alloy steel, the hook is suitable for use with Grade 100 or Grade 80 chain.



*The handle hilt provides added protection of user's hand*

*Positive lock latch is self-locking when hook is loaded*

*Replaceable pull-trigger for easy operation of the positive self-lock latch*

*The SHUR-LOC® Handle Eye Hook allows the user to get a confident grip on any load. Handle opening big enough to accommodate a gloved hand*

*Recessed trigger design better protects the trigger from potential damage*

S-1316AH SHUR-LOC® Handle Eye Hook

S-1316AH SHUR-LOC® Handle Eye Hook						
Chain Size		Working Load Limit 4:1	Working Load Limit 5:1	Frame Code	Weight Each	Stock Number
(in.)	(mm)					
5/8	16	22,600 (lbs) 10.3 (t)	18,080 (lbs) 8.2 (t)	JA	18 (lbs) 8.2 (kgs)	1023579
3/4	18/20	35,300 (lbs) 16.0 (t)	28,240 (lbs) 12.8 (t)	KA	28 (lbs) 12.7 (kgs)	1023599
7/8	22	42,700 (lbs) 19.4 (t)	34,160 (lbs) 15.5 (t)	LA	39 (lbs) 17.7 (kgs)	1023607
1	26	59,700 (lbs) 27.1 (t)	47,760 (lbs) 21.7 (t)	NA	60 (lbs) 27.2 (kgs)	1023625





# S-13326AH SHUR-LOC® Handle Swivel Hook with Bearing

www.thecrosbygroup.com

## MORE CONTROL WITH SMOOTHER OPERATIONS

- Bearing lubricated with long-lasting lithium-based grease
- Bearing gives better control over load
- The SHUR-LOC® handle hook allows the user to get a confident grip on any load
- Handle opening big enough to accommodate a gloved hand
- Replaceable pull-trigger for easy operation of the positive self-lock latch

*Low friction bearing for better positioning load when lifted*

*Positive lock latch is self-locking when hook is loaded*

*Handle hilt provides added protection of user's hand*

*Recessed trigger design better protects the trigger from potential damage*



S-13326AH SHUR-LOC Handle Swivel Hook with Bearing						
Chain Size		Working Load Limit 4:1	Working Load Limit 5:1	Frame Code	Weight Each	Stock Number
(in.)	(mm)					
5/8	16	22,600 (lbs) 10.3 (t)	18,080 (lbs) 8.2 (t)	JA	26 (lbs) 11.8 (kgs)	1005014
3/4	18/20	35,300 (lbs) 16.0 (t)	28,240 (lbs) 12.8 (t)	KA	37 (lbs) 16.8 (kgs)	1005023
7/8	22	42,700 (lbs) 19.4 (t)	34,160 (lbs) 15.5 (t)	LA	57 (lbs) 25.9 (kgs)	1005041
1	26	59,700 (lbs) 27.1 (t)	47,760 (lbs) 21.7 (t)	NA	84 (lbs) 38.1 (kgs)	1005050

9992485 1/18/17

S-13326AH SHUR-LOC® HANDLE SWIVEL HOOK with Bearing

