

## McKissick® Overhead Bridge Crane Blocks

- Wide range of products available (see tables below).
- Removable housing allows block to be reeved without complete disassembly.
- Bearing life and Design Factors meet:
  - ASME HST-4, Class H
  - CMAA 70 Class D
  - FEM9.511 Class 2m
  - ISO 4301.1 Class M5
- Adjustable sheave spacing in 1/2" increments (1/4" on 6-1/2" size).
- Sheave pitch diameter minimum of 16 times rope diameter on standard sizes.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, contain the patented **QUIC-CHECK®** markings and come with a world class latch that integrates with hook tip.
- **U.S. Patent 7,255,330**
- All sizes are **RFID EQUIPPED**.
- Sheave bearings are maintenance free and sealed for life (10,000 hrs.).
- Ability to attach optional anti two-block device.
- Available with shackle as lower connection point.
- Ultimate load is 5 times the Working Load Limit.

Key to McKissick® Easy-Lift® Overhead Bridge Crane Blocks					
Single and Double Sheave Blocks				Double Sheave Blocks Only	
<b>BC</b>	<b>05</b>	<b>D</b>	<b>08</b>	<b>B</b>	<b>36</b>
↓	↓	↓	↓	↓	↓
McKissick® 750 Series Bridge Crane Blocks	Working Load Limit (t)	Number of Sheaves S = 1 D = 2	Sheave Diameter (in)	Center Pin Designation	Sheave Spacing in 1/8" Increments



**BC-751**  
Single  
Sheave

### BC-751 Single Sheave

Model 751 – Single Sheave						
WLL (t)	2	3	5	7.5	10	
Sheave O.D.	6.5" 165mm	8" 203mm	10" 254mm	12" 305mm	14" 356mm	
Pitch Diameter	5.69" 151mm	7.38" 187mm	9.25" 235mm	11" 279mm	12.5" 318mm	
Wireline*						
1/4" 6.5mm						
5/16" 8mm						
3/8" 9 - 10mm						
7/16" 11mm						
1/2" 12 - 13mm						
9/16" 14mm						
5/8" 16mm						
3/4" 19mm						
7/8" 22mm						
1" 25 - 26mm						

\* Additional Wireline sizes available.

### BC-752 Double Sheave

Model 752 – Double Sheave					
WLL (t)	3	5	7.5	10	15
Sheave O.D. (mm)	6.5" 165mm	8" 203mm	10" 254mm	12" 305mm	14" 356mm
Sheave Spacing Centerline (mm)	3.25" - 5" 82.6 - 127mm	4.5" - 6.5" 114 - 165mm	5.25" - 7.75" 133 - 203mm	6.5" - 10" 165 - 254mm	7.5" - 11" 191 - 279mm
Pitch Diameter (mm)	5.95" 150 - 152mm	7.38" 183 - 191mm	9.25" 228 - 236mm	11" 273 - 282mm	11" 273 - 282mm
Wireline*					
1/4" 6.5mm					
5/16" 8mm					
3/8" 9 - 10mm					
7/16" 11mm					
1/2" 12 - 13mm					
9/16" 14mm					
5/8" 16mm					
3/4" 19mm					

\* Additional Wireline sizes available.

= Primary Wireline Size

= Other Wireline Sizes



**BC-752**  
Double Sheave