

WELL LOGGER'S BLOCKS



475
Floor Block



477
Floor Block



476
Top Block

- Alloy aluminum housing for maximum strength and minimum weight.
- Conductor cable ONLY is recommended for use with Well Logger's Blocks.
- For use in high speed well logging, perforating, etc.
- Extra large double row, pre-adjusted sealed tapered bearing.
- Quick opening pin for fast string-up, light weight for easy handling.



475 / 477 Floor Blocks

Sheave Diam. (in)	Block No.	Floor Block Stock No.	Working Load Limit (Tons)*	Conductor Cable Size (in)†	Weight Each (lb)	Connection
7	475	180020	1-1/2	3/16	10	Swivel Hanger
10	475	180253	2-1/2	5/16	21	Swivel Hanger
12	475	180440	2-1/2	5/16	24	Swivel Hanger
14	475	180618	2-1/2	5/16	43	Swivel Hanger
14	477	169784	6	1/4	58	Swivel Clevis
20	477	191072	6	1/4	70	Swivel Clevis
24	477	191107	10	5/16	130	Swivel Clevis

* Ultimate Load is 4 times the Working Load Limit.

† Other cable sizes available upon request.

476 Top Blocks

Sheave Diam. (in)	Block No.	Top Block Stock No.	Working Load Limit (Tons)*	Conductor Cable Size (in)	Weight Each (lb)	Connection
7	476	180075	2-1/2	3/16	10	Stinger Pin
10	476	180333	4	5/16	21	Stinger Pin
12	476	180529	4	5/16	24	Stinger Pin
14	476	180707	4	5/16	43	Stinger Pin

* Ultimate Load is 4 times the Working Load Limit.