

SPECIFICATION SHEET FOR CROSBY HR125, HR125M, HR1000 HOIST RINGS WITH OPTIONAL BOLT LENGTHS

Date:	
CG #:	Crosby Quote Number:
Customer #:	Contact:
Distributor's Name:	Distributor's Fax Number:
Distributor's Phone Number:	Quantity Requested:
Distributor's P.O. #	Crosby Representative:

- Determine the *Type of Threads* required on the Hoist Ring - Metric or UNC, UNF, etc. **NOTE - NOT DESIGNED FOR PIPE, ACME OR TAPERED THREADS.**
- Determine the *Working Load Limit* of the requested Hoist Ring.
- Determine *Bolt Diameter* - The diameter of the required bolt.
- Determine *Effective Thread Length* - This is the length the threads must be in order to fully engage, or project through, the work piece. **NOTE; If the Effective Thread Length is not known, the Length of Bolt is required.**
- Determine *Length of the Bolt* - The overall length of the bolt as measured from under the head of the bolt. **NOTE: If the Effective Thread Length is not known, the Length of the bolt is required.**
- # of Thread Threads per Inch (Length Between Threads for Metric threads)* - This information is required to ensure we ship proper bolt size (i.e., 1/2 - 13, 7/8 - 9, 8 x 1.25, etc.).

1. → **Thread Type** (Circle One)
 UNC Thread
 Metric Thread
 Other
(NOT DESIGNED FOR PIPE, ACME, OR TAPERED THREADS)
2. → Hoist Ring Capacity
 (Working Load Limit)
 _____ lb/kgs

