

790 SERIES METRIC EASY REEVE® HOOK BLOCKS

- Wide range of product available.
 - Capacity: 4,5 to 72t - Larger Models Available.
 - Sheave Sizes: 254 to 508mm.
 - Wireline Sizes: 11 to 28mm.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, and have the patented **QUIC-CHECK®** markings (Duplex hooks are available on most sizes).
- Design factor of 4:1 (unless otherwise noted).
- All Easy Reeve® Blocks are furnished standard with Roller Bearings.
- Reeving Guides Standard – All Models.
- Blocks thru 20t use 319N hooks with S-4320 latches..
- Sheave lubrication through center pin - separate lube channel to each bearing.
- Sheaves fully protected by side plates.
- Dual action hook (swings and rotates).
- Repair parts available through worldwide distribution network.
- All Easy Reeve® blocks, 4406mm and larger, are furnished with McKissick® Roll-Forged™ sheaves with flame hardened grooves.
- Manufactured by an ISO 9001 and API Q1 certified facility .
- “Look for the Orange Hook . . . the mark of genuine McKissick® quality”.



Center “Dead End”
to promote better block travel under various reeving configurations



OPTIONS AVAILABLE

- DIN 15402 Hooks - “Rams Horn”
- Swivel Tee and Shackle Assemblies
- Sheave Shrouds
- Heavy Duty Latch
- Third party testing with Certification available upon request
- McKissick Split-Nut® retention system



Flat Bottom side plate for self standing during reeving process.

