



## COMPONENTS



### Crosby KUPLEX Kuplink KS

Alternative Master Link for single leg slings with the need for a Kupler.


Crosby Stock No.	Reference	WLL (t)		Dimensions (mm)					Weight (kg)
		8	8+10	A	B	R	D	S	
2780388	KS7N	1.5	2	152	76	178	17	13	.64
2780397	KS10N	3.2	4	152	76	190	22	16	1.15
2780404	KS13N	5.3	6.7	178	108	220	28	21	2.13
2780413	KS16N	8	10	228	127	285	38	27	4.69



### Crosby KUPLEX Reeveable Egg Link KSS

The ideal link for collar slings – fully reeveable and compact.


Crosby Stock No.	Reference	WLL (t)		Dimensions (mm)					Weight (kg)
		8	8+10	A	B	R	D	S	
2780422	*KSS7N	1.5	2	70	35	92	14	10	.27
2780431	KSS10N	3.2	4	102	51	132	19	14	.74
2780440	KSS13N	5.3	6.7	137	67	177	26	20	1.92
2780459	KSS16N	8	10	172	83	220	32	24	3.17
2780468	KSS19N	11.2	14	203	98	261	38	28	5.58
2780477	KSS23N	16	21	238	114	305	40	38	8.42
2780486	KSS26N	21.2	27	273	133	351	46	46	14.51



### Crosby KUPLEX Kupler K

This component is used for joining chain to the top link.


Crosby Stock No.	Reference	WLL (t)		Dimensions (mm)				Weight (kg)
		8	8+10	R	W	D	S	
2780495	K7N	1.5	2	60	26	12	10	.15
2780501	K10N	3.2	4	73	35	19	15	.47
2780510	K13N	5.3	6.7	95	45	25	22	1.01
2780529	K16N	8	10	118	54	28	23	1.66
2780538	K19N	11.2	14	134	64	34	28	2.78
2780547	K23N	16	21	121	64	45	38	4.26
2780556	K26	21.2	27	140	82	48	45	6.30
2780574	K32	31.5	40	175	96	64	51	11.48



### Crosby KUPLEX Component Connector TLN

A general purpose link for connecting chain to eye-type components. The TL is currently a Grade 8 component.

Crosby Stock No.	Reference	WLL (t)		Dimensions (mm)					Weight (kg)
		8	8+10	A	B	C	D	E	
2780583	TL7N	1.5	-	67	49	48	14.3	9	.11
2780592	TL10N	3.2	-	89	66	70	19.2	13	.36
2780609	TL13N	5.3	-	118	85	85	26.5	17	.66
2780618	TL16N	8	-	144	96	106	32	19	1.08
2780627	TL19N	11.2	-	168	115	122	38.5	23	1.77
2780636	TL23N	16	-	206	140	150	49	28	2.8
2780645	TL26N	21.2	-	230	163	166	57	32	4.4
2780654	TL32N	31.5	-	278	210	200	63	39	8.4



### Crosby KUPLEX Chain Connector KJ

A flexible link for chain connection and suitable for making up endless slings. The KJ is currently a Grade 8 component.

Crosby Stock No.	Reference	WLL (t)		Dimensions (mm)					Weight (kg)
		8	8+10	A	B	C	D	E	
2780663	KJ7	1.5	-	56	34	41	8	7.5	.09
2780672	KJ10	3.2	-	73	45	51	11.5	11	.27
2780681	KJ13	5.3	-	94	61	65	14.7	14	.44
2780690	KJ16	8	-	120	75	84	19.1	18	.83
2780707	KJ19	11.2	-	142	90	100	22.9	21	1.42